

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Gingivamoll paint liquid

Revision date: 25.07.2018

Product code: 10498

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Gingivamoll paint liquid

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Epithesis material for use in dentistry.

1.3. Details of the supplier of the safety data sheet

Company name:	DETAX GmbH & Co. KG	
Street:	Carl-Zeiss-Strasse	
Place:	D-76275 Ettlingen	
Telephone:	+49 7243/510-0	Telefax: +49 7243/510-100
e-mail:	post@detax.de	
Internet:	www.detax.de	
Responsible Department:	Emergency number:	

+49 7243/510-0
This number is only obtainable during office hours (Monday - Thursday 8.00 a.m. - 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)

1.4. Emergency telephone number:

+49 7243/510-0
This number is only obtainable during office hours (Monday - Thursday 8.00 a.m. - 5.00 p.m., Friday 8.00 - 4.00 p.m.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Aspiration hazard: Asp. Tox. 1

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements


Regulation (EC) No. 1272/2008

Hazard components for labelling

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha

Signal word: Danger

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Gingivamoll paint liquid

Revision date: 25.07.2018

Product code: 10498

Page 2 of 8

H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use Carbon dioxide (CO ₂), Foam, Extinguishing powder to extinguish.
P391	Collect spillage.
P403+P235	Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of aliphatic hydrocarbons.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha			80 - 100 %
	265-151-9	649-328-00-1		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Induce vomiting when the affected person is not unconscious. Medical treatment necessary. Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).

4.2. Most important symptoms and effects, both acute and delayed

No information available.

according to Regulation (EC) No 1907/2006

Gingivamoll paint liquid

Revision date: 25.07.2018

Product code: 10498

Page 3 of 8

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: @0102.B010927. Pyrophoric or self-heating substances. Oxidising agent

Further information on storage conditions

Keep only in the original container in a cool, dry and well-ventilated place, away from foodstuffs.

according to Regulation (EC) No 1907/2006

Gingivamoll paint liquid

Revision date: 25.07.2018

Product code: 10498

Page 4 of 8

7.3. Specific end use(s)

Liquid for coating of silicone based epithesis.
For use by trained specialist staff.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable are gloves of the following material: NBR (Nitrile rubber)

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid:	
Colour:	light yellow	
Odour:	characteristic	

pH-Value:		not determined
-----------	--	----------------

Changes in the physical state

Melting point:	< -30 °C
Initial boiling point and boiling range:	40-60 °C
Flash point:	<-31 °C

Flammability

Solid:	not applicable
Gas:	not applicable
Lower explosion limits:	0,7 vol. %
Upper explosion limits:	8,3 vol. %
Ignition temperature:	245 °C

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable

according to Regulation (EC) No 1907/2006

Gingivamoll paint liquid

Revision date: 25.07.2018

Product code: 10498

Page 5 of 8

Decomposition temperature: not determined

Oxidizing properties

Not oxidizing.

 Vapour pressure: 350 hPa
(at 20 °C)

 Density (at 20 °C): 0,65 g/cm³

Water solubility: 0,002 g/L

Solubility in other solvents

not determined

Partition coefficient: not determined

 Viscosity / kinematic: 0,76 mm²/s
(at 25 °C)

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with : spontaneously flammable and combustible materials.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Higher temperatures advance the formulation of explosive vapour-air mixtures, therefore don't expose the product to increased temperatures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha				
	oral	LD50 2000 mg/kg	Rat		
	dermal	LD50 4000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 54 mg/l	Rat		

according to Regulation (EC) No 1907/2006

Gingivamoll paint liquid

Revision date: 25.07.2018

Product code: 10498

Page 6 of 8

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways. (Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha)

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Not identified as PBT/ vPvB substances

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number:**

UN 1268

14.2. UN proper shipping name:

PETROLEUM DISTILLATES, N.O.S.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Gingivamoll paint liquid

Revision date: 25.07.2018

Product code: 10498

Page 7 of 8

14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L/ 30 kg
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Other applicable information (land transport)

Contains: petroleum ether

Marine transport (IMDG)

14.1. UN number:	UN 1268
14.2. UN proper shipping name:	PETROLEUM DISTILLATES, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Marine pollutant:	P
Limited quantity:	1 L/ 30 kg
EmS:	F-E, S-E

Other applicable information (marine transport)

Flash point: < -31°C c.c.

Contains petroleum ether

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1268
14.2. UN proper shipping name:	PETROLEUM DISTILLATES, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Limited quantity Passenger:	1 L/ 30 kg
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

Other applicable information (air transport)

Contains petroleum ether

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Water contaminating class (D):	2 - clearly water contaminating

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Gingivamoll paint liquid

Revision date: 25.07.2018

Product code: 10498

Page 8 of 8

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Gewerblich	-	-	-	-	-	-	-	2

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)