Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name : INCIDIN LIQUID

Product code : 117483E

Use of the : Surface Disinfectant

Substance/Mixture

Substance type: : Mixture

For professional users only.

Product dilution information : No dilution information provided.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Professional spray and wipe no gloves

Recommended restrictions

on use

: Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.

PO Box 11; Winnington Avenue

Northwich, Cheshire, United Kingdom CW8 4DX

+ 44 (0)1606 74488 ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone : +441618841235

number +32-(0)3-575-5555 Trans-European

Date of Compilation/Revision : 14.09.2020 Version : 1.6

Section: 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226 Eye irritation, Category 2 H319 Specific target organ toxicity - single exposure, Category 3, H336

Central Nervous System

The classification of this product is based on toxicological assessment.

2.2 Label elements

117483E 1 / 15

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapour.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Precautionary Statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P261 Avoid breathing spray.

P280e Wear eye protection/face protection.

2.3 Other hazards

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration:
	EC-No.	REGULATION (EC) No 1272/2008	[%]
	REACH No.		
Isopropyl Alcohol	67-63-0 200-661-7 01-2119457558-25	Flammable liquids Category 2; H225 Eye irritation Category 2; H319 Specific target organ toxicity - single exposure Category 3; H336	>= 30 - < 50
propan-1-ol	71-23-8 200-746-9 01-2119486761-29	Flammable liquids Category 2; H225 Serious eye damage Category 1; H318 Specific target organ toxicity - single exposure Category 3; H336	>= 25 - < 30
Substances with a workp	lace exposure limit :		
Propylene glycol	57-55-6	Not Classified;	>= 1 - < 2.5
	200-338-0		
	01-2119456809-23		
	• • • • • • • •	1. (1.1. 0(1 0 0(1 4.0	

For the full text of the H-Statements mentioned in this Section, see Section 16.

4.1 Description of first aid measures

Section: 4. FIRST AID MEASURES

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for

at least 15 minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Get medical attention.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

117483E 2 / 15

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention

if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Fire Hazard

Keep away from heat and sources of ignition. Flash back possible over considerable distance.

Beware of vapours accumulating to form explosive concentrations.

Vapours can accumulate in low areas.

Hazardous combustion

products

: Depending on combustion properties, decomposition products

may include following materials:

Carbon oxides

5.3 Advice for firefighters

for firefighters

Special protective equipment : Use personal protective equipment.

Further information : Use water spray to cool unopened containers. Fire residues and

> contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or

explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency

personnel

: Remove all sources of ignition. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in

sections 7 and 8.

Advice for emergency

responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable

materials.

6.2 Environmental precautions

117483E 3/15

Environmental precautions : Do not allow contact with soil, surface or ground water.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to

do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain

material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.

For personal protection see section 8.

See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes. Use only with adequate

ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Wash hands thoroughly after handling. Open drum carefully as content may be under pressure. Do not breathe spray, vapour. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear

full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after

handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Keep away from heat and sources of ignition. Keep in a cool, well-ventilated place. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable

labeled containers.

Storage temperature : 0 °C to 25 °C

7.3 Specific end uses

Specific use(s) : Professional spray and wipe no gloves

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Isopropyl Alcohol	67-63-0	TWA	400 ppm	UKCOSSTD

117483E 4 / 15

				999 mg/m3	
			STEL	500 ppm	UKCOSSTD
				1,250 mg/m3	
propan-1-ol	71-23-8		STEL	250 ppm	UKCOSSTD
				625 mg/m3	
Further information	Sk	Can b	e absorbed through the	e skin. The assigned substances	are those for
		which	there are concerns that	t dermal absorption will lead to	systemic toxicity.
			TWA	200 ppm	UKCOSSTD
				500 mg/m3	
Further information	Sk	Can b	e absorbed through the	e skin. The assigned substances	are those for
		which	there are concerns that	t dermal absorption will lead to	systemic toxicity.
Propylene glycol	57-55-6		TWA (particles)	10 mg/m3	UKCOSSTD
			TWA (Total vapour	150 ppm	UKCOSSTD
			and particles)	474 mg/m3	

DNEL

DNEL	
Isopropyl Alcohol	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 888 mg/cm2 End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 500 mg/m3 End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 319 mg/cm2 End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 89 mg/m3 End Use: Consumers Exposure routes: Inpestion Potential health effects: Long-term systemic effects Value: 26 ppm
Propylene glycol	: End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 168 mg/m3 End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 10 mg/m3 End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 50 mg/m3 End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects

117483E 5 / 15

Value: 10 mg/m3

End Use: Consumers Exposure routes: Dermal

Potential health effects: Long-term systemic effects

Value: 213 mg/cm2

End Use: Consumers Exposure routes: Ingestion

Potential health effects: Long-term systemic effects

Value: 85 ppm

PNEC

PINEC La arranda Alabahat	1	Freely western
Isopropyl Alcohol	:	Fresh water
		Value: 140.9 mg/l
		Marina water
		Marine water
		Value: 140.9 mg/l
		Intermittent use/release
		Value: 140.9 mg/l
		Fresh water
		Value: 552 mg/kg
		value. 332 mg/kg
		Marine sediment
		Value: 552 mg/kg
		value. 552 mg/Ng
		Soil
		Value: 28 mg/kg
		- 555g
		Sewage treatment plant
		Value: 2251 mg/l
		- s.u.o
		Oral
		Value: 160 mg/kg
		5 5
Propylene glycol	:	Fresh water
		Value: 260 mg/l
		Marine water
		Value: 26 mg/l
		Intermittent use/release
		Value: 183 mg/l
		Fresh water sediment
		Value: 572 mg/kg
		Market and Proceed
		Marine sediment
		Value: 57.2 mg/kg
		Sawaga traatment plant
		Sewage treatment plant
		Value: 20000 mg/l
		Soil
		LOUI

117483E 6 / 15

INCIDIN LIQUID | Value: 50 mg/kg

8.2 Exposure controls

Appropriate engineering controls

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations

below occupational exposure standards.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

Eye/face protection (EN 166) : Safety glasses with side-shields

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection

(EN 14605)

: No special protective equipment required.

Respiratory protection (EN

143, 14387)

: When respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization, consider the use of certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, with filter type:A

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : light yellow
Odour : alcohol-like
pH : 8.0, 100 %

Flash point : 25 °C closed cup

Odour Threshold : Not applicable and/or not determined for the mixture

Melting point/freezing point : Not applicable and/or not determined for the mixture

Initial boiling point and : Not applicable and/or not determined for the mixture

boiling range

Evaporation rate : Not applicable and/or not determined for the mixture

Flammability (solid, gas) : Not applicable and/or not determined for the mixture Upper explosion limit : Not applicable and/or not determined for the mixture

117483E 7 / 15

Lower explosion limit : Not applicable and/or not determined for the mixture Vapour pressure : Not applicable and/or not determined for the mixture

Relative vapour density : Not applicable and/or not determined for the mixture

Relative density : 0.89
Water solubility : soluble

Solubility in other solvents : Not applicable and/or not determined for the mixture Partition coefficient: n- : Not applicable and/or not determined for the mixture

octanol/water

Auto-ignition temperature : Not applicable and/or not determined for the mixture

Thermal decomposition : Not applicable and/or not determined for the mixture

Viscosity, kinematic : Not applicable and/or not determined for the mixture

Explosive properties : Not applicable and/or not determined for the mixture

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials: Carbon oxides

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of : Inhalation, Eye contact, Skin contact

exposure

117483E 8 / 15

Product

Acute oral toxicity : There is no data available for this product.

Acute inhalation toxicity : There is no data available for this product.

Acute dermal toxicity : There is no data available for this product.

Skin corrosion/irritation : No skin irritation

Method: OECD Test Guideline 404
Test substance: Similar Product

Serious eye damage/eye

irritation

: Irritating to eyes.

Method: OECD Test Guideline 405 Test substance: Similar Product

Respiratory or skin

sensitization

: There is no data available for this product.

Carcinogenicity : There is no data available for this product.

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : Isopropyl Alcohol

LD50 rat: 5,840 mg/kg

propan-1-ol

LD50: 1,870 mg/kg

Propylene glycol

LD50 rat: 22,000 mg/kg

Components

Acute inhalation toxicity : Isopropyl Alcohol

4 h LC50 rat: > 30 mg/l Test atmosphere: vapour

propan-1-ol

4 h LC50 : 26.76 mg/l Test atmosphere: dust/mist

Propylene glycol

4 h LC50 rat: > 158.5 mg/l Test atmosphere: dust/mist

Components

117483E 9 / 15

Acute dermal toxicity : Isopropyl Alcohol

LD50 rabbit: 12,870 mg/kg

propan-1-ol

LD50: 4,032 mg/kg

Potential Health Effects

Eyes : Causes serious eye irritation.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Inhalation may cause central nervous system effects.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : Redness, Pain, Irritation

Skin contact : No symptoms known or expected.

Ingestion : No symptoms known or expected.

Inhalation : Dizziness, Drowsiness

Section: 12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Environmental Effects : This product has no known ecotoxicological effects.

Product

Toxicity to fish : no data available Toxicity to daphnia and other : no data available

aquatic invertebrates

Toxicity to algae : no data available

Components

Toxicity to fish : Isopropyl Alcohol

96 h LC50 Pimephales promelas (fathead minnow): 9,640 mg/l

propan-1-ol

96 h EC50: 3,800 mg/l

Propylene glycol

96 h LC50: > 10,000 mg/l

Components

Toxicity to daphnia and other : Isopropyl Alcohol

aquatic invertebrates LC50 Daphnia magna (Water flea): > 10,000 mg/l

propan-1-ol

48 h LC50: 1,000 mg/l

117483E 10 / 15

Propylene glycol

48 h EC50: 18,340 mg/l

Components

Toxicity to algae : propan-1-ol

48 h EC50: 9,170 mg/l

Propylene glycol

96 h EC50: 19,000 mg/l

12.2 Persistence and degradability

Product

no data available

Components

Biodegradability : Isopropyl Alcohol

Result: Readily biodegradable.

propan-1-ol

Result: Readily biodegradable.

Propylene glycol

Result: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be

either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or

higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product : Where possible recycling is preferred to disposal or incineration. If

recycling is not practicable, dispose of in compliance with local

117483E 11 / 15

regulations. Dispose of wastes in an approved waste disposal facility.

: Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Guidance for Waste Code

Contaminated packaging

selection

: Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number : 1987

: ALCOHOLS, N.O.S. 14.2 UN proper shipping

name

(Isopropanol, Propanol)

14.3 Transport hazard : 3

class(es)

14.4 Packing group : 111 14.5 Environmental hazards : No 14.6 Special precautions for : None

user

Air transport (IATA)

14.1 UN number : 1987

14.2 UN proper shipping : Alcohols, n.o.s.

name

(Isopropanol, Propanol)

14.3 Transport hazard : 3

class(es)

: 111 14.4 Packing group 14.5 Environmental hazards : No : None 14.6 Special precautions for

user

Sea transport (IMDG/IMO)

14.1 UN number : 1987

14.2 UN proper shipping : ALCOHOLS, N.O.S.

name

(Isopropanol, Propanol)

14.3 Transport hazard

class(es)

: 111 14.4 Packing group 14.5 Environmental hazards : No 14.6 Special precautions for : None

user

: Not applicable. 14.7 Transport in bulk

117483E 12 / 15

according to Annex II of MARPOL 73/78 and the IBC Code

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply)

Regulations.

The Control of Substances Hazardous to Health Regulations.

Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Flammable liquids 3, H226	Based on product data or assessment
Eye irritation 2, H319	Based on product data or assessment
Specific target organ toxicity - single exposure	Calculation method
3, H336	

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Full text of other abbreviations

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM -American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL -Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number -European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response; GHS - Globally Harmonized System: GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA – International Air Transport Association; IBC – International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 -Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International

117483E 13 / 15

Convention for the Prevention of Pollution from Ships; n.o.s. – Not Otherwise Specified; NO(A)EC – No Observed (Adverse) Effect Concentration; NO(A)EL – No Observed (Adverse) Effect Level; NOELR – No Observable Effect Loading Rate; NZIoC – New Zealand Inventory of Chemicals; OECD – Organization for Economic Co-operation and Development; OPPTS – Office of Chemical Safety and Pollution Prevention; PBT – Persistent, Bioaccumulative and Toxic substance; PICCS – Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH – Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT – Self-Accelerating Decomposition Temperature; SDS – Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: Professional spray and wipe no gloves

Life Cycle Stage : Widespread use by professional workers

Product category : PC35 Washing and cleaning products (including solvent based

products)

Contributing scenario controlling environmental exposure for:

Environmental release : **ERC8a** Wide dispersive indoor use of processing aids in open

category systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment : Municipal sewage treatment plant

Plant

Contributing scenario controlling worker exposure for:

Process category : **PROC11** Non industrial spraying

Exposure duration : 480 min

117483E 14 / 15

Operational conditions and

: Indoor

risk management measures

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour

1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC19** Hand-mixing with intimate contact and only PPE

available

Exposure duration : 480 min

Operational conditions and risk management measures

Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

117483E 15 / 15